

Technical Info	
Style Name	A LVT Loft Collection
Style Number	JMW7161
Application	Residential/Light Commercial/Commercial Vinyl Tile
Class	ASTM F3261 Class III Printed Film Vinyl Plank Type B (Embossed)
Standard wear layers*	12mil (0.3mm); 20mil (0.5mm); 27mil (0.7mm)
Standard thicknesses (overall)*	3.5mm; 4mm; 4.5mm; 5mm
Standard formats*	6" x 48" nominal; 7"x 48" nominal; 9" x 48" nominal 7" x 60" nominal; 9" x 60" nominal
IXPE Sound Proof Backing	0.5mm; 1mm; 1.5mm
Installation	Floating

	6" x 48"			7" x 48"		
Packaging	3.5mm	4.5mm	5.0mm	3.5mm	4.5mm	5.0mm
Ft ² per carton	CALL FOR PACKAGING DETAILS					
Pieces per carton						

Performance Data	
Resilient Floor Covering Institute	FloorScore® certified
ASTM F970 Static Load Limit	Passes; ≥250 psi
ASTM C1028 Coefficient of Friction	Dry .81 / Wet .80
ASTM F2199 Dimensional Stability	Passes; no greater than .51mm/305mm
ASTM F1914 Residual Indent	Passes; average less than 8%
ASTM F925 Resistance to Chemicals	Passes; no change
ASTM F2055 Squareness	Passes; maximum deviation of .25mm
ASTM F2055 Size & Tolerance	Passes; no greater than .4mm/305mm
ASTM F1514 Resistance to Heat	Passes; Average $\Delta E^*_{ab} \leq 8.0$
NALFA Castor Chair Resistance	No visible damage – 25,000 revolutions
ISO 16000 parts -3, -6, -9, -11	A+ VOC Emissions Class
ISO 9000 Quality Management	Production conforms to ISO 9001:2008

Warranty Information	12mil	20mil	27mil
Wear Layer Warranty, Residential	10 year	15 year	25 year
Wear Layer Warranty, Commercial	N/A	15 year (limited/light)	20 year (limited)

Contact Information	
Email	info@aproductUS.com
Phone	(888) 203-0054

Material supply or manufacturing processes may require changes to this information without notice.