



A | LVT The Color Collection Luxury Glue Down

Technical Info	
Style Name	A LVT The Color Collection
Style Number	APLD
Application	Light Commercial/Commercial Vinyl Tile
Class	ASTM F1700 Class III Printed Film Vinyl Plank Type B (Embossed)
Standard wear layers*	20mil (0.5mm) 27 Mil(0.7)
Standard thicknesses (overall)*	2.5mm; 3.0mm
Standard formats*	6" x 36" nominal (152mm x 914mm); 18" x 18" nominal (457mm x 457mm)
Finish	Urethane
Installation	Glue down

*Custom configurations available upon request including size and embossing options.

	6" x 36" (152mm x 914mm)	18" x 18" (457mm x 457mm)
Packaging	3.0mm	3.0mm
Ft ² per carton	26.92 SF/CTN	31.5 SF/CTN
Pieces per carton	18 PCS/CTN	14 PCS/CTN

Performance Data	
Resilient Floor Covering Institute	FloorScore® certified
ASTM F970 Static Load Limit	Passes; ≥250 psi
ASTM C1028 Coefficient of Friction	Dry .81 / Wet .80
ASTM F2199 Dimensional Stability	Passes; no greater than .51mm/305mm
ASTM F1914 Residual Indent	Passes; average less than 8%
ASTM F925 Resistance to Chemicals	Passes; no change
ASTM F2055 Squareness	Passes; maximum deviation of .25mm
ASTM F2055 Size & Tolerance	Passes; no greater than .4mm/305mm
ASTM F1514 Resistance to Heat	Passes; Average $\Delta E^*_{ab} \leq 8.0$
NALFA Castor Chair Resistance	No visible damage – 25,000 revolutions
ISO 16000 parts -3, -6, -9, -11	A+ VOC Emissions Class
ISO 9000 Quality Management	Production conforms to ISO 9001:2008

Warranty Information	12mil	20mil	27mil
Wear Layer Warranty, Residential	15 year	25 year	30year
Wear Layer Warranty, Commercial	5 year (limited/light)	10 year (limited)	15 year (limited)
Supplemental Warranty	5 year	10 year	10 year

Contact Information	
Email	info@aproductUS.com
Phone	(888) 203-0054

