





The A|LVT Loft Collection offers 9 looks with a design spectrum suitable for many styles and applications.

Stone Polymer Composite (SPC) & ABA Constructed Rigid Clic: Simple, fast, clean, and versatile installation.

SONANCE: Closed cell non-absorbent sound reduction padding.

A|LVT products are low maintenance with no polishing sealing, or waxing required, water proof and sound resistant.

Each look features a durable, abrasion resistant wear layer for a beautiful appearance that lasts many years.

All A LVT patterns are available in Rigid Clic System All colors and patterns are available for shipment

Technical Info

Wear Layer 12 mil residential 20 mil light commercial

27 mil commercial

Thickness

4 mm 4.5 mm 5 mm

IXPE Sound Control Backing (mm) $0.5 \; \text{mm}$

1 mm

1.5 mm

Standard Sizes 6 x 48 in

7 x 48 in 9 x 48 in 12 x 24 in $7 \times 60 in$ 9 x 60 in

Composition **UV** Coating top layer

Wear layer Decor film SPC Rigid core SONANCE Cushion pad

Click system

Performance Data

ASTMF1700 ASTM F2055 Size Squareness ASTM F385 Thickness

Thickness of wear layer ASTM F410 **ASTM F1914** Residual indentation

ASTM F137 Flexibility

ASTM F2199 Dimension stability ASTM F925 Resistance to Chemical **ASTM F1514** Resistance to heat **ASTM F1515** Resistance to light

OTHER TEST ITEMS

nalfa/ansi lf/iso4918 castor chair resistance

ASTM E2179 ASTM E492 sound insullation

ASTM E90 **ASTM D2047**

ASTM C1028 static Coefficient

ASTM F510 **ASTM D4060** Abasion Resistance **ASTM F970** static load ASTM D903 Peel Strength ASTM G21 Resistance to Fungi ASTM F963 Heavy Metal Elements

ASTM E84 ASTM E648 Fire Testing







ASTM E662





Loft Collection



Carytown



Ocean Park



* LoDo



* Princeville



Seatack*

^{*} Handscraped * Deep Wood Embossed



Audubon Park



Park View



Marigny



Condesa*

^{*} Handscraped * Deep Wood Embossed

