



LVT

The ALVT collection offers 12 urban wood looks and 6 urban stone looks with a design spectrum suitable for many styles and applications.

Luxury Glue Down system: provides a strong and long-lasting permanent installation with a lower life-cycle cost.

ACC Clic system: simple, fast, clean, and versatile installation.

ALVT products are low maintenance with no polishing, sealing, or waxing required. Each look features a durable, abrasion resistant wear layer for a beautiful appearance that lasts many years.



URBAN WOODS



Hampden W078





Adams Morgan W093



NoDa W095



West Loop W072



North End W069



Mission District W010



Bushwick W092



Bowery W076



Hillcrest W110



Echo Park W077





URBAN STONES



South Street L033



Thames Street S214



U Street S328



Madison Avenue S408



Ocean Drive L419



14th Street S014

All ALVT patterns are available in Luxury Glue Down and ACC Clic systems. A LVT patterns in the Luxury Glue Down system are available through our stocking program.

Technical Info

Wear Layer 8 mil residential

> 12 mil light commercial 20 mil commercial

Overall thickness

2mm residential **Luxury Glue Down system** 2.5mm commercial

> Overall thickness 1.5mm **A|LVT** + 4.5mm ACC ACC Clic system 1.5mm A LVT + 5mm ACC

2mm A|LVT + 5mm ACC

Standard Sizes 6" x 48" (157mm x 1242mm)

12" x 24" (305mm x 611mm) 10" x 60" (253mm x 1530mm)

Warranty (wear layer) 8 mil / 10 year residential

> 12 mil / 5 year limited commercial / 15 year residential 20 mil / 10 year limited commercial / 25 year residential

Composition Top Layers: PU coating, embossing in register, easy to

maintain, no need to polish, seal, or wax.

Film Layer: sharp and detailed print layer provides a

realistic character and unique appearance.

Backing: vinyl backing, durable & flexible, resistant to

pressure, environmentally friendly.

Supplemental Warranty Ardex SystemOne™ up to 10 years

Stocking Program A LVT maintains stock in each of our most popular styles.

Contact an A|LVT rep for select styles. (888) 203-0054 | info@aproductUS.com

Performance Data

RFCI FloorScore® certified

ASTM F970 Static Load Limit Passes; ≥250 psi **ASTM C1028 Coefficient of Friction** Dry .81 / Wet .80

ASTM F2199 Dimensional Stability Passes; no greater than .51mm/305mm

ASTM F1914 Residual Indent Passes; average less than 8%

ASTM F925 Resistance to Chemicals Passes: no change

> **ASTM F2055 Squareness** Passes; maximum deviation of .25mm Passes; no greater than .4mm/305mm

ASTM F2055 Size & Tolerance

ASTM F1514 Resistance to Heat Passes; Average $\Delta E^*ab \leq 8.0$

No visible damage - 25,000 revolutions **NALFA Castor Chair Resistance**

ISO 16000 parts -3, -6, -9, -11 A+ VOC Emissions Class

ISO 9000 Quality Management Production conforms to ISO 9001:2008











