



URBAN WALLS

888.203.0054
 aproductus.com
 info@aproductus.com
 A | Tile by A | Product



Technical Specifications

Usage	INDOOR
Material Type	CERAMIC WALL TILE
Thickness	6mm (12x12 mosaic)/ 7mm (2x8, 4x4, 3x6, 6x6, 9.5x13) / 7.3mm (3x12, 4x10, 4x10BV)/ 8mm (4x16, 6x18, 13x4)
Standard Sizes	13" x 14", 6" x 18", 4 1/4" x 16", 9.5" x 13", 6" x 8", 4" x 12", 4 1/4" x 10", 3" x 12", 6" x 6", 4 1/4" x 4 1/4", 3" x 6", 2" x 8", 12"x12" Mosaic
Finish	MATTE / BRIGHT

Packaging Information

	PCS / CTN	SF / CTN	SF / PLT	LBS / PLT
4 x 12 Wall Tile	32	12.60	800	2000
4 1/4 x 4 1/4 Wall Tile	80	10.00	600/ 700	1464/ 1,640.80
6 x 6 Wall Tile	50	12.50	600.00	1440.00
3 x 6 Wall Tile	80	10.00	600/ 720	1353.60/ 1728
3 x 12 Wall Tile	50	12.59	1246.78	3029.40
4x10 Wall Tile	38	11.25	877.37	2110.37
4 x 16 Wall Tile	23	11.00	792.00	2070.00
6 x 18 Wall Tile	16	12.00	1152.00	3127.30
9.5 x 13 Wall Tile	30	25.57	997.44	2272.14
13 x 24 Wall Tile	11	23.49	750.90	1375.68
6 x 8 Wall Tile	27	9.00	396/ 792	926.64/ 1853.28
2 x 8 Wall Tile	60	6.45	775.00	1785.60
12 x 12 Mosaic Sheet (2x2 tile)	20	20	1080	3240

	ASTM TEST	ISO TEST	VALUE REQUIRED ANSI	DECLARED ASTM
Water Absorption	C373	ISO-10545/3	7% < wa <=20%	>10%
Break Strength	C648	ISO-10545/4	>=250	Meets or Exceeds
Shade and Texture Rating	CTDA "V"	-	-	V1
Chemical Resistance	C650	ISO-10545/13	Unaffected	Unaffected
Scratch Hardness	MOH's Scale	EN-101	-	3
Warpage	C485	ISO-10545/2	0.0075	Pass
Wedging	C502	ISO-10545/2	1.0% Max	Pass

Performance Data

Abrasion Resistance PB5	Class 4
Frost Resistance	Resistant

Warranty Information

Warranty	1 year
Supplemental Warranty	Ardex SystemOne™ Tile & Stone Warranty (up to 25 years)



Material supply or manufacturing processes may require changes to this information without notice.